



CS107 ADHESIVE

DESCRIPTION:

CS107 is a versatile, sprayable, solvent based contact adhesive.

CS107 is suitable for bonding varying materials to themselves and substrates.

TYPICAL FEATURES | BENEFITS:

- Tough, yet resilient bond.
- Solvent based, therefore tacks up rapidly.
- Will adhere well to timber | metals | fabrics.
- Will adhere well on concrete and/or timber.

PERFORMANCE DATA:

Element		Value
Minimum Application Temperature:	~ Air	+10°C
Maximum Operating Temperature:		+80°C
Flash Point:		-22°C
Adhesion Properties to correctly prepared surface:	~ Fabrics ~ Metals ~ Timbers	Excellent Excellent Excellent
Type:		Sprayable contact adhesive
Base:		Polychloroprene rubber / resin
Adhesive Solids:		18 - 22%
SG kg/litre:		0.85
Colour:		Red
Thinning:		May be thinned with small amounts of Solvent HA
Coverage:		Approximately 6m ² per litre /per surface (3m² of bonded area per litre)
Open Time:	+25°C –50%RH	1 – 10 minutes <i>Dependent upon atmospheric conditions, air movement, air temperature and the porosity of the substrate.</i>
Clean Up:		When wet, Solvent HA <i>(Do not spill onto floor coverings as the solvents are strong and very difficult to remove or will surface stain the finished flooring).</i>
Dangerous Goods Class:		Refer: SDS
Packaging:		4 litre tin 20 litre metal pail
Shelf life:		6 months from date of manufacture when stored in an unopened container at 5 – 30°C **Must not Freeze** <i>After this period consult with DGL Bondlast Construction Products.</i>

RECOMMENDED USES:

- Metal foils.
- Commercial flooring vinyl.
- Plastic laminates to themselves or to timber or particle board.
- Polyurethane foams.
- Carpets.
- Timber veneers.

NOT RECOMMENDED:

- Application to uncured concrete (*Minimum Cure 28 days*).
- Application to unstable substrates.
- CS107 is not suitable for expanded polystyrene foams.
- Do not apply onto waterproofing membranes.
- CS107 is solvent based; take care that solvent sensitive backings on materials will not be damaged.
- Application to wet or damp substrates.
- Staining is possible on some materials.
- Not suitable on or with solvent sensitive materials.
- For bonding untested materials.

SUBSTRATE PREPARATION:

It is essential that the surfaces to be bonded are dry and clean.	
Surface Preparation:	All traces of dust, oil and dirt must be removed; it may be necessary to wipe surfaces with Solvent HA.

APPLICATION METHOD:

Spray Roller Brush Spreader	
Stir adhesive thoroughly prior to use: <i>A small amount only of Solvent HA may be added to thin if necessary.</i>	
Application:	The rapid drying of the solvent in cold/damp conditions may cause blooming (water condensation on the surface – a whitening effect). This will affect adhesion. Improve forced air ventilation or warm the area or wait until the blooming dissipates. ● Apply a uniform coat of adhesive on both surfaces to be bonded. ● Allow adhesive to dry until it feels slightly tacky to the touch. <i>(This will take 1 – 10 minutes depending on porosity of materials and ambient temperature).</i> ● On porous surfaces (<i>e.g. edges of particle board</i>), it is desirable to apply a second coat of adhesive. ● Once the adhesive has dried to the slightly tacky stage, the materials may be joined immediately or up to 30 minutes later. ● Accurately position the surfaces to be bonded then bring the coated surfaces together with smooth, firm pressure. ● Final bond strength will be obtained after 48 hours. ● Rolling with a square edge or round edge heavy hand roller will dramatically improve adhesion.

HEALTH & SAFETY: *Refer safety data sheets (SDS).*

- Wear appropriate safety equipment and clothing
- Contains potentially strong solvents (toluene, ketones, and aliphatic hydrocarbons). Breathing of vapour should be avoided.
- Use organic vapour masks, particularly in confined spaces.
- The use of fans to provide positive forced air draft and/or extraction is recommended.
- Do not use CS107 near naked flames, electric heaters, electric motors, or other sources of ignition such as gas pilot lights.
- Avoid skin contact.

ADHESIVE RANGE:

Solvent-based

Product	Type	Colour	Application Method	Installation Type
CB103	Brushable Contact	Straw	Brush Roller	Various – Refer Technical Literature
CS110	Sprayable Contact	Straw	Brush Roller Spray	Various – Refer Technical Literature
CS107	Sprayable Contact	Red	Brush Roller Spray	Various – Refer Technical Literature
Roberts 6037	Trowel Grade	Cream	Trowel	Garage & Outdoor Carpet
Quicktack	Trowel Grade	Cream	Trowel	Garage & Outdoor Carpet

Water-based

Product	Type	Colour	Application Method	Installation Type
Duracryl HSV	Acrylic	Off-white	Trowel	Vinyl – all types Vinyl Planks ¹
Supacryl	Acrylic - Zero VOC	White	Trowel	Vinyl – all types Vinyl Planks
Truestik VA1	Acrylic - Zero VOC	Off-white	Trowel	Vinyl – all types Vinyl Planks
Supatack T9 -Gen 2	Acrylic	Off-white	Trowel	Vinyl – all types Vinyl Planks
Garatack	Acrylic	Off-white	Trowel	Carpet
Goldstix	Latex-based	Off-white	Trowel	Carpet
Bondstix	Latex-based	Off-white	Trowel	Carpet
RMA 2000 CTA	Acrylic	Pink	Trowel Roller	Carpet Tiles Polystyrene

Epoxy | Polyurethane

Product	Type	Colour	Application Method	Installation Type
NPU Adhesive	2-part Polyurethane	Beige	Trowel	Various – Refer Technical Literature
Truestik EA	2-part Epoxy	Green	Trowel	Various – Refer Technical Literature ²

Footnotes:

1 Recommended adhesive for vinyl plank

2 Recommended adhesive for vinyl planks in areas exposed to solar heat gain.

FLOOR LEVELLING COMPOUND RANGE:

Patch Repairs

Product	Application Thickness	Mix Additive	Application Area	Use
Bondlast Rapid Patch 40	0 - 100mm in a single application	Water	Interior	Rapid Set
Hardfast (White Patch)	0 - 20mm in a single application	Water	Interior	Divots Isolated patching only

Bulk Fill

Screed 20 +	10 - 100mm in single application	Water	Interior	Heavy Duty Bulk Fills - Ramps
Bondlast Rapid Screed	5 - 200mm in a single application	Water	Interior / Exterior	Rapid Set Shower Falls

Two-Part Screed

Durabond Superfine	0 - 5mm in a single application	Latex Emulsion	Interior	General Purpose - Fine Finish
--------------------	---------------------------------	----------------	----------	-------------------------------

Self-Levelling

Bondlast Super Level 30	0 - 12mm in single application Self-Smoothing at >3mm	Water	Interior	Self-Levelling Installations
-------------------------	--	-------	----------	------------------------------

Fine Feather Finish

Bondlast Super Feather Patch	0 - 3mm in single application Very fine finishing	Water	Interior	Fine Smoothing of floors
------------------------------	--	-------	----------	--------------------------

Date: June 2024
Replaces Sept 2021

DGL Bondlast Construction Products, a Division of DGL Manufacturing NZ
Auckland Office: 24-28 Lady Ruby Drive, East Tamaki, phone: 09-267-2772.
Auckland Trade Store: 308 Church Street, Penrose, phone: 09-583-6258.
Hamilton Trade Store: 18 Somerset Street, Frankton, phone: 07-847-8658.
Wellington Trade Store: Unit 9A, 4 Glover Street, Ngauranga Gorge, phone: 04-240-0305.
Christchurch Trade Store: 112 Carlyle Street, Sydenham, phone: 03-366-6802.
Customer Service: 0508-882-288 sales.bondlast.cp@dglgroup.com
Website: www.bondlastconstruction.com

DISCLAIMER: This information appearing in this Document (**Details**) concerning the product which is the subject of the Document (**Product**) is either based on present technical knowledge and tests done by Bondlast or tests done by, and data supplied from third parties including you, the customer. Since the actual use by you and by others of the Product is beyond the control of Bondlast, no warranty or representation, express or implied is made by Bondlast regarding the suitability for such use, nor does Bondlast accept any liability arising out of the use by you of other products or materials, whether third party or not, that may be referred to in this Document. Bondlast recommends that you carry out your own tests as to the suitability of the Product for your purpose, regarding which you accept full responsibility. In addition, if any of the Details appearing in the Document are based upon tests done by, and/or data supplied by any third party, Bondlast provides no warranties or representations in connection with those Details and you, the customer waives any right you may have against Bondlast in connection with the accuracy, completeness or otherwise of the Details. The information in this Document is not to be construed as absolutely complete or accurate since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations affecting use of the Product. Bondlast does not provide any warranty or representation to you that the Product does not infringe the intellectual property rights of any third party. All orders accepted shall be subject to the standard conditions of sale of Bondlast which are on the back of our invoice. In accepting the Product, you, the customer acknowledges and agree **a.)** The Product is or may be of a hazardous nature and that you, the customer, are responsible for the disposal of the container housing the Product in accordance with the requirements and regulations of the relevant supervising government. **b.)** The Product has a limited shelf life and must be stored strictly in accordance with the guidelines and specifications related to it. **c.)** Where the Details relate to Product tested by Bondlast, those Details are indicative only, regarding which there may be batch to batch variation. **d.)** Bondlast gives no warranty or representation as to the applicability for the particular use by you, the customer, of the Product and you the customer shall be responsible for ensuring that the Product is fit for your intended use. **e.)** Bondlast's liability for breach of any term, condition, guarantee or warranty (express or implied and concerning the information in this Document or the Product more generally) including any liability for direct or indirect consequential loss (including indirect loss of profits), is limited to the maximum extent permitted by law and, at Bondlast's election, to either replacing or repairing the goods or paying the cost of replacing or repairing the goods, or in the case of services, supplying the services again.